

CO₂ Inkubator Smart Biotherm

Description

Unit provides a six-sided heating: the heating elements are located on the walls and on the door, thus providing excellent uniform temperature distribution, regardless of external factors, such as ambient temperature and positioning of the device.

Built-in infrared CO₂ sensor allows accurate control of the CO₂ level. The sensor makes measurement non-sensitive to changes in temperature and humidity inside the incubator.

The chamber is made of stainless steel with smoothed seams to minimize contamination and to facilitate cleaning.

The unit is equipped with a UV air recirculation system. One UV lamp and a fan are mounted behind the rear wall, providing decontamination of the working volume.

A convenient access port is built in the wall of the incubator for easy output of wire sensors or devices' installed inside. The access port is heated independently to prevent formation of condensate.

Unit is equipped with error tracing and alarm systems, which significantly lower potential risks during operation.

Unit is equipped with a "black box" system that records temperature, humidity and CO₂ levels, as well as statuses for door opening, UV lamp, fan and errors, to the inner memory.

Bluetooth connection to PC is available.

Features

- Six-sided heating provides uniform distribution of the temperature inside the chamber
- Infrared CO₂ sensor, non-sensitive to temperature and humidity changes
- UV recirculation system for decontamination cycles
- Bluetooth data transfer to PC
- «Black box» parameter logging system
- Error tracing and alarm system
- Separately heated lockable port for chamber access for cables



CO₂ Incubator Smart



CO₂ incubator Smart with shaker CPS-20

CO₂ Inkubator Smart Biotherm

Technical Data

Working chamber material	Stainless Steel (1 mm)
Temperature setting range	+25°C – 60°C
Temperature stability	±0.1°C
Temperature uniformity at +37°C	±0.3°C
Working volume	46 liters
Number of shelves	3 (max. 6)
Presence of the inner glass door	Yes
Relative humidity	> 90% @ 37°C
Humidity delivery	Water pan
CO ₂ control range*	0 – 20%
CO ₂ sensor	Infrared CO ₂ sensor
Temperature and CO ₂ level input	Digital
UV lamp	1 x 6 W, TUV G6T5
Data output	Bluetooth
Access port	1 (Ø 26 mm)
Dimensions	400 x 410 x 580 mm
Weight	37.7 kg
Nominal operating voltage	230 V, 50/60 Hz
Power consumption	600 W
Order No.	104.1950

Option Shaker CPS-20



Orbital CO₂ Shaker

CPS-20 shaker is specifically designed for use in challenging environments such as CO₂ and humidity. It ensures reproducible results in cell cultivation.

CPS-20 provides smooth orbital movement of the platform and is perfect for use in the CO₂ incubator.

Order No.: 105.1216